NSN 5915-00-999-4911

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-999-4911

| Occasional Harington |
|---|
| Overall Height: |
| 3.872 inches |
| Body Length: |
| 2.687 inches |
| Body Width: |
| 2.312 inches |
| Body Height: |
| 2.718 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.125 inches |
| Vibration Resistance Range In Hertz: |
| +10.0/+55.0 |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.750 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Average Life Rating In Hours: |
| 2500.0 |
| Reference Frequency Per Function: |
| 17.5 hertz blank |
| Source Impedance Rating Per Function: |
| 5.0 kilohms blank |
| Load Impedance Per Function: |
| 500.0 ohms blank |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 1 threaded stud |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 4.4 blank |
| Functional Terminal Type And Quantity: |
| 1 turret output 2nd function |
| Specified Frequencies Of Discrimination Per Function: |
| 11.00 hertz blank and 15.00 hertz blank and 20.00 hertz blank and 24.00 hertz blank |
| Thread Size: |
| 0.138 inches |
| Frequency Band Width Per Function: |
| 15.00 hertz blank and 20.00 hertz blank |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |

20.0 blank and 1.5 blank and 1.5 blank and 20.0 blank

NSN 5915-00-999-4911

Band Pass Filter - Page 2 of 2



| Style Designator: |
|---|
| Rectangular terminal/terminals on opposite surfaces |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Demilitarization

No

Fiig:

A047b0