

View Online at https://aerobasegroup.com/nsn/5915-01-005-0048

Overall Height:
2.750 inches
Body Length:
2.000 inches
Body Width:
0.750 inches
Body Height:
2.125 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.500 inches
Input Impedance Per Function W/load:
50.0 ohms 1st radio interference
Output Impedance Per Function W/source Across Input:
50.0 ohms 1st radio interference
Power Line Frequency Rating Per Function In Hertz:
400.0 2nd radio interference
Operating Current Rating Per Function In Amps:
5.0 2nd radio interference
Principal Circuitry Type Per Function:
Inductance-capacitance 2nd radio interference
Mounting Facility Screw Thread Series Designator:
mounting racinty Screw rifead Series Designator.
Unc
Unc
Unc Inclosure Type:
Unc Inclosure Type: Encased
Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole Functional Terminal Type And Quantity:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 230.0 volts ac 2nd radio interference 2nd function
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 230.0 volts ac 2nd radio interference 2nd function Thread Size:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 230.0 volts ac 2nd radio interference 2nd function Thread Size: 0.138 inches
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 230.0 volts ac 2nd radio interference 2nd function Thread Size: 0.138 inches Body Material:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 230.0 volts ac 2nd radio interference 2nd function Thread Size: 0.138 inches Body Material: Metal
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 230.0 volts ac 2nd radio interference 2nd function Thread Size: 0.138 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 230.0 volts ac 2nd radio interference 2nd function Thread Size: 0.138 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 2.1 kilovolts at sea level
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 230.0 volts ac 2nd radio interference 2nd function Thread Size: 0.138 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 2.1 kilovolts at sea level Style Designator:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded hole Functional Terminal Type And Quantity: 2 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 230.0 volts ac 2nd radio interference 2nd function Thread Size: 0.138 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 2.1 kilovolts at sea level Style Designator: Rectangular terminal/terminals on opposite surfaces

AeroBase Group

Demilitarization:

No

Fiig:

A047b0