

View Online at <https://aerobasegroup.com/nsn/5915-01-007-8841>

Overall Length:

2.300 inches

Body Outside Diameter:

0.360 inches

Vibration Resistance Range In Hertz:

+5.0/+55.0

Operating Temperature Range:

-40.0/+71.0 degrees celsius

Reference Frequency Per Function:

11.4 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.6 blank

Average Power Rating Per Function:

1.0 watts blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

0.6 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 11.40 gigahertz blank and 13.20 gigahertz blank and 15.60 gigahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 11.40 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.0 hertz blank and 11.4 gigahertz blank

Unpackaged Unit Weight:

4.000 ounces

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0