

View Online at <https://aerobasegroup.com/nsn/5915-01-008-0230>

Overall Height:

1.000 inches

Body Length:

3.000 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.375 inches

End Application:

R-1884/glq rcvr

Reference Frequency Per Function:

18.5 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Voltage Standing Wave Ratio Per Function:

1.8 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

2 pin ground and 1 pin input and 1 pin output

Specified Frequencies Of Discrimination Per Function:

16.40 megahertz blank and 20.60 megahertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

17.00 megahertz blank and 20.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

6.0 blank and 1.5 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

17.0 megahertz blank and 20.0 megahertz blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

81349-mil-f-18327c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0