

View Online at <https://aerobasegroup.com/nsn/5915-01-008-4766>

Overall Length:

Between 0.781 inches and 0.843 inches

Body Length:

Between 0.438 inches and 0.498 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Average Life Rating In Hours:

1000.0

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

400.0 blank

Operating Current Rating Per Function In Amps:

10.0 blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

15.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encased

Width Across Flats:

Between 0.235 inches and 0.265 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Functional Terminal Type And Quantity:

1 wire lead input 1st function

Operating Voltage Rating And Type Per Function:

140.0 volts ac blank and 200.0 volts dc blank

Thread Size:

0.216 inches

Maximum Dielectric Withstanding Dc Voltage:

1.0 kilovolts at sea level

Style Designator:

Round terminal/terminals on opposite surfaces

Test Data Document:

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-15733/35 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0