

View Online at <https://aerobasegroup.com/nsn/5915-01-008-8580>

Overall Height:

1.015 inches

Body Length:

3.800 inches

Body Width:

2.600 inches

Body Height:

0.640 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.200 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.000 inches

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Average Life Rating In Hours:

20000.0

Reference Frequency Per Function:

287.6 kilohertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

5.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

286.60 kilohertz blank and 287.55 kilohertz blank and 287.65 kilohertz blank and 288.60 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

287.55 kilohertz blank and 287.65 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 1.0 blank and 1.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0