

View Online at <https://aerobasegroup.com/nsn/5915-01-010-1536>

**Overall Height:**

0.851 inches

**Body Length:**

2.734 inches

**Body Width:**

0.500 inches

**Body Height:**

0.580 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.500 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Operating Temperature Range:**

-32.0/+68.0 degrees celsius

**Reference Frequency Per Function:**

455.0 kilohertz blank

**Source Impedance Rating Per Function:**

600.0 ohms blank

**Load Impedance Per Function:**

600.0 ohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

7.0 blank

**Functional Terminal Type And Quantity:**

2 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

453.00 kilohertz blank and 454.50 kilohertz blank and 455.50 kilohertz blank and 457.00 kilohertz blank

**Thread Size:**

0.112 inches

**Frequency Band Width Per Function:**

454.50 kilohertz blank and 455.50 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

**Body Surface Treatment:**

Gold

**Precious Material And Location:**

Body and contact surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0