

View Online at <https://aerobasegroup.com/nsn/5915-01-010-1536>

Overall Height:

0.851 inches

Body Length:

2.734 inches

Body Width:

0.500 inches

Body Height:

0.580 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.500 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-32.0/+68.0 degrees celsius

Reference Frequency Per Function:

455.0 kilohertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Load Impedance Per Function:

600.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

7.0 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

453.00 kilohertz blank and 454.50 kilohertz blank and 455.50 kilohertz blank and 457.00 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

454.50 kilohertz blank and 455.50 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

Body Surface Treatment:

Gold

Precious Material And Location:

Body and contact surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0