

View Online at https://aerobasegroup.com/nsn/5915-01-013-4502

Overall Length: 39.875 inches Overall Height: 7.500 inches Overall Width: 27.875 inches Body Length: 39.875 inches Body Vidth: 27.875 inches Body Width: 24.875 inches Body Width: 24.875 inches Unthreaded Mounting Hole Diameter: 0.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 28.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 26.375 inches Operating Tempurature Range: -30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Diol-10 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Maximum Voltage Drop Per Func
Overall Heigh: 7.500 inches Overall Width: 27.875 inches Body Length: 39.875 inches Body Width: 24.875 inches Dotywall Width: 24.875 inches Unthreaded Mounting Hole Diameter: 0.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 28.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 28.000 inches Operating Tempurature Range: -30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Poreating Current Rating Per Function In Hertz: 60.0 3rd radio interference Maximum Voltage Drop Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole
7.500 inches Overall Width: 27.875 inches Body Length: 39.875 inches Body Width: 24.875 inches Doty Width: 24.875 inches Unthreaded Mounting Hole Diameter: 0.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 28.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 28.000 inches Operating Tempurature Range: -30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Poreating Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole
Overall Width:27.875 inchesBody Length:39.875 inchesBody Width:24.875 inchesUnthreaded Mounting Hole Diameter:0.375 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Length:28.000 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Length:26.375 inchesOperating Tempurature Range:-30.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms 3rd radio interferenceLoad Impedance Per Function:50.0 ohms 2nd radio interferencePower Line Frequency Rating Per Function In Hertz:60.0 3rd radio interferenceDotardia interference100.0 3rd radio interference2.0 volts ac 3rd radio interferenceHourting Facility Type And Quantity:4 unthreaded holeFunctional Terminal Type And Quantity:
27.875 inches Body Length: 39.875 inches Body Width: 24.875 inches Unthreaded Mounting Hole Diameter: 0.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 28.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 26.375 inches Operating Tempurature Range: -30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Derating Current Rating Per Function In Hertz: 60.0 3rd radio interference Doperating Current Rating Per Function In Hertz: 60.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Hacisure Type: Encased Mounting Facility Type And Quantity:
Body Length: 39.875 inches Body Width: 24.875 inches Unthreaded Mounting Hole Diameter: 0.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 28.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 28.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 26.375 inches Operating Tempurature Range: -30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Operating Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Mounting Facility Type And Quantity: Encased Mounting Facility Type And Quantity:
39.875 inches Body Width: 24.875 inches Unthreaded Mounting Hole Diameter: 0.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 28.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 26.375 inches Operating Tempurature Range: -30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Porting Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole <
Body Width: 24.875 inches Unthreaded Mounting Hole Diameter: 0.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 28.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 28.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 28.375 inches Operating Tempurature Range: -30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Operating Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
24.875 inches Unthreaded Mounting Hole Diameter: 0.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 28.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 28.375 inches Operating Tempurature Range: -30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Operating Current Rating Per Function In Hertz: 60.0 3rd radio interference Doparting Current Rating Per Function In Amps: 100.0 3rd radio interference Aximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Encased Mounting Facility Type And Quantity:
Unthreaded Mounting Hole Diameter:0.375 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Length:28.000 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width:28.075 inchesOperating Tempurature Range:-30.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms 3rd radio interferenceLoad Impedance Per Function:50.0 ohms 2nd radio interferencePower Line Frequency Rating Per Function In Hertz:60.0 3rd radio interferenceOperating Current Rating Per Function In Amps:100.0 3rd radio interferenceMaximum Voltage Drop Per Function:2.0 volts ac 3rd radio interferenceHonsen Type:EncasedMounting Facility Type And Quantity:4 unthreaded holeFunctional Terminal Type And Quantity:
0.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 28.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 26.375 inches Operating Tempurature Range: -30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Operating Current Rating Per Function In Hertz: 60.0 3rd radio interference Dopating Current Rating Per Function In Amps: 100.0 3rd radio interference 2.0 volts ac 3rd radio interference Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Type And Quantity:
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 28.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 26.375 inches Operating Tempurature Range: -30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Operating Current Rating Per Function In Hertz: 60.0 3rd radio interference Doperating Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
28.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 26.375 inches Operating Tempurature Range: -30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Operating Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 26.375 inches Operating Tempurature Range: -30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Operating Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
26.375 inches Operating Tempurature Range: -30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Operating Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
Operating Tempurature Range:-30.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms 3rd radio interferenceLoad Impedance Per Function:50.0 ohms 2nd radio interferencePower Line Frequency Rating Per Function In Hertz:60.0 3rd radio interferenceOperating Current Rating Per Function In Amps:100.0 3rd radio interferenceMaximum Voltage Drop Per Function:2.0 volts ac 3rd radio interferenceInclosure Type:EncasedMounting Facility Type And Quantity:4 unthreaded holeFunctional Terminal Type And Quantity:
-30.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Operating Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
Source Impedance Rating Per Function: 50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Operating Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
50.0 ohms 3rd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Operating Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
Load Impedance Per Function:50.0 ohms 2nd radio interferencePower Line Frequency Rating Per Function In Hertz:60.0 3rd radio interferenceOperating Current Rating Per Function In Amps:100.0 3rd radio interferenceMaximum Voltage Drop Per Function:2.0 volts ac 3rd radio interferenceInclosure Type:EncasedMounting Facility Type And Quantity:4 unthreaded holeFunctional Terminal Type And Quantity:
50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 3rd radio interference Operating Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
Power Line Frequency Rating Per Function In Hertz:60.0 3rd radio interferenceOperating Current Rating Per Function In Amps:100.0 3rd radio interferenceMaximum Voltage Drop Per Function:2.0 volts ac 3rd radio interferenceInclosure Type:EncasedMounting Facility Type And Quantity:4 unthreaded holeFunctional Terminal Type And Quantity:
60.0 3rd radio interference Operating Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
Operating Current Rating Per Function In Amps: 100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
100.0 3rd radio interference Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
Maximum Voltage Drop Per Function: 2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
2.0 volts ac 3rd radio interference Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
Inclosure Type: Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
Encased Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
Mounting Facility Type And Quantity: 4 unthreaded hole Functional Terminal Type And Quantity:
4 unthreaded hole Functional Terminal Type And Quantity:
O three deal studies ut dat function
3 threaded stud input 1st function
Maximum Dielectric Withstanding Ac Rms Voltage:
500.0 volts at sea level
Operating Voltage Rating And Type Per Function:
250.0 volts ac 3rd radio interference 3rd function
Special Features:
Terminals located on opposite ends of filter
Style Designator:
Rectangular terminal/terminals on opposite surfaces

Radio Frequency Interference Filter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0