NSN 5915-01-014-0336

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-014-0336

Overall Height:

1.250 inches

Body Length:

3.750 inches

Body Width:

1.000 inches

Body Height:

0.978 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.350 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.600 inches

Operating Tempurature Range:

-35.0/+80.0 degrees celsius

Reference Frequency Per Function:

200.0 hertz blank

Source Impedance Rating Per Function:

1.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.5 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 400.00 hertz blank and 2.40 kilohertz blank and 125.00 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 400.00 hertz blank

NSN 5915-01-014-0336

Low Pass Filter - Page 2 of 2



Discrimination At Specificationified Frequencies Per Function In Decibels:

1.5 blank and 1.5 blank and 105.0 blank and 105.0 blank

Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0