NSN 5915-01-014-2289

Low Pass Filter - Page 1 of 2



Low 1 ass 1 liter 1 age 1 of 2
View Online at https://aerobasegroup.com/nsn/5915-01-014-2289
Overall Length:
2.218 inches
Overall Height:
1.218 inches
Body Length:
2.000 inches
Body Width:
0.850 inches
Body Height:
1.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.500 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Operating Tempurature Range:
-30.0/+105.0 degrees celsius
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
2.3 kilohertz blank
Source Impedance Rating Per Function:
5.0 kilohms blank
Load Impedance Per Function:
5.0 kilohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
2 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
2.0 blank

2.0 Diaini

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

50.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 4.60 kilohertz blank and 12.50 kilohertz blank and 50.00 kilohertz blank

Thread Size:

0.112 inches

NSN 5915-01-014-2289

Low Pass Filter - Page 2 of 2

A047b0



Body Material:	
Metal	
Frequency Band Width Per Function:	
1.00 hertz blank and 4.60 kilohertz blank	
Discrimination At Specificationified Frequencies Per Function In Decibels:	
3.0 blank and 3.0 blank and 130.0 blank and 112.0 blank	
Style Designator:	
Rectangular terminal/terminals on two surfaces	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	