

View Online at <https://aerobasegroup.com/nsn/5915-01-014-4832>

**Overall Height:**

Between 0.730 inches and 0.770 inches

**Body Length:**

Between 1.750 inches and 1.765 inches

**Body Width:**

Between 0.850 inches and 0.865 inches

**Body Height:**

Between 0.570 inches and 0.590 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.440 inches and 1.460 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Operating Temperature Range:**

+9.0/+65.0 degrees celsius

**Reference Frequency Per Function:**

20.0 megahertz blank

**Source Impedance Rating Per Function:**

4.7 kilohms blank

**Load Impedance Per Function:**

4.7 kilohms blank

**Principal Circuitry Type Per Function:**

Crystal blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

2 pin ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

15.00 megahertz blank and 19.975 megahertz blank and 20.025 megahertz blank and 25.00 megahertz blank

**Thread Size:**

0.086 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

19.975 megahertz blank and 20.025 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0