

View Online at <https://aerobasegroup.com/nsn/5915-01-015-8306>

Overall Height:

0.700 inches

Body Length:

4.030 inches

Body Width:

2.380 inches

Body Height:

0.510 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.500 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.750 inches

Operating Temperature Range:

-18.0/+75.0 degrees celsius

Average Life Rating In Hours:

26280.0

Reference Frequency Per Function:

941.0 single high pass hertz

Source Impedance Rating Per Function:

1.0 kilohms 2nd band pass

Load Impedance Per Function:

100.0 kilohms 5th band pass

Principal Circuitry Type Per Function:

Inductance-capacitance 3rd band pass 3rd function

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

14 pin

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 2nd band pass

Functional Terminal Type And Quantity:

5 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

747.00 hertz 2nd band pass 2nd function and 755.00 hertz 2nd band pass 2nd function and 785.00 hertz 2nd band pass 2nd function and 794.00 hertz 2nd band pass 2nd function

Body Material:

Metal

Frequency Band Width Per Function:

922.00 hertz 4th band pass and 959.00 hertz 4th band pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 3rd band pass 3rd function and 30.0 3rd band pass 3rd function

Body Surface Treatment:

Tin

Unpackaged Unit Weight:

8.000 ounces

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0