

View Online at <https://aerobasegroup.com/nsn/5915-01-015-8306>

**Overall Height:**

0.700 inches

**Body Length:**

4.030 inches

**Body Width:**

2.380 inches

**Body Height:**

0.510 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.500 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.750 inches

**Operating Temperature Range:**

-18.0/+75.0 degrees celsius

**Average Life Rating In Hours:**

26280.0

**Reference Frequency Per Function:**

941.0 single high pass hertz

**Source Impedance Rating Per Function:**

1.0 kilohms 2nd band pass

**Load Impedance Per Function:**

100.0 kilohms 5th band pass

**Principal Circuitry Type Per Function:**

Inductance-capacitance 3rd band pass 3rd function

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

14 pin

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 2nd band pass

**Functional Terminal Type And Quantity:**

5 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

747.00 hertz 2nd band pass 2nd function and 755.00 hertz 2nd band pass 2nd function and 785.00 hertz 2nd band pass 2nd function and 794.00 hertz 2nd band pass 2nd function

**Body Material:**

Metal

**Frequency Band Width Per Function:**

922.00 hertz 4th band pass and 959.00 hertz 4th band pass

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 3rd band pass 3rd function and 30.0 3rd band pass 3rd function

**Body Surface Treatment:**

Tin

**Unpackaged Unit Weight:**

8.000 ounces

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0