

View Online at <https://aerobasegroup.com/nsn/5915-01-021-5562>

Overall Height:

Between 0.565 inches and 0.580 inches

Body Length:

0.775 inches

Body Width:

0.425 inches

Body Height:

0.440 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.575 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.250 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

70.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

5 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

3 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

69.45 megahertz blank and 69.96 megahertz blank and 70.04 megahertz blank and 70.55 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

69.96 megahertz blank and 70.04 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 blank and 3.0 blank and 3.0 blank and 30.0 blank

Maximum Dielectric Withstanding Dc Voltage:

25.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0