

View Online at <https://aerobasegroup.com/nsn/5915-01-023-7672>

Overall Height:

0.350 inches

Body Length:

0.760 inches

Body Width:

0.460 inches

Body Height:

0.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.600 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.300 inches

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Reference Frequency Per Function:

500.0 hertz blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

1.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Inclosure Type:

Encapsulated

Mounting Facility Type And Quantity:

4 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 1.00 kilohertz blank and 2.50 kilohertz blank and 3.00 kilohertz blank

Body Material:

Plastic

Frequency Band Width Per Function:

1.00 hertz blank and 1.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 39.0 blank and 52.0 blank

Unpackaged Unit Weight:

3.000 grams

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0