## NSN 5915-01-023-8288

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-023-8288

Overall Length:
3.450 inches
Body Length:
3.050 inches
Body Width:
1.050 inches
Body Height:
1.700 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.900 inches
Vibration Resistance Range In Hertz:
+5.0/+500.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.900 inches
Operating Tempurature Range:
-5.0/+75.0 degrees celsius
Reference Frequency Per Function:
1.5 kilohertz blank
Input Impedance Per Function W/load:
50.0 ohms blank
Output Impedance Per Function W/source Across Input:
50.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
8 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
0.5 blank
Functional Terminal Type And Quantity:
2 pin output 2nd function
Specified Frequencies Of Discrimination Per Function:
1.00 kilohertz blank and 3.00 kilohertz blank and 150.00 kilohertz blank and 1.60 megahertz blank
Thread Size:
0.112 inches
Body Material:
Metal
Frequency Band Width Per Function:
1.00 kilohertz blank and 3.00 kilohertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 3.0 blank and 28.0 blank and 120.0 blank

## NSN 5915-01-023-8288

Low Pass Filter - Page 2 of 2



r:
ľ

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0