

View Online at <https://aerobasegroup.com/nsn/5915-01-024-0843>

Overall Length:

2.875 inches

Overall Height:

1.188 inches

Body Length:

1.875 inches

Body Width:

0.750 inches

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.500 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.470 inches

Operating Temperature Range:

+0.0/+50.0 degrees celsius

Reference Frequency Per Function:

5.64 gigahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Principal Circuitry Type Per Function:

Electromechanical blank

Voltage Standing Wave Ratio Per Function:

1.5 blank

Average Power Rating Per Function:

1.8 watts blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

6.1 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

5.624 gigahertz blank and 5.6365 gigahertz blank and 5.6435 gigahertz blank and 5.656 gigahertz blank

Frequency Band Width Per Function:

5.6365 gigahertz blank and 5.6435 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

20.0 blank and 3.0 blank and 3.0 blank and 20.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

5.6386 gigahertz blank and 5.6414 gigahertz blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0