

View Online at https://aerobasegroup.com/nsn/5915-01-025-0861

Overall Length: 11.000 inches Overall Height: 3.500 inches Body Length: 8.000 inches Body Width: Between 2.970 inches and 3.030 inches Unthreaded Mounting Hole Diameter: Between 0.276 inches and 0.283 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 9.000 inches
Overall Height: 3.500 inches Body Length: 8.000 inches Body Width: Between 2.970 inches and 3.030 inches Unthreaded Mounting Hole Diameter: Between 0.276 inches and 0.283 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
3.500 inches Body Length: 8.000 inches Body Width: Between 2.970 inches and 3.030 inches Unthreaded Mounting Hole Diameter: Between 0.276 inches and 0.283 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Body Length:8.000 inchesBody Width:Between 2.970 inches and 3.030 inchesUnthreaded Mounting Hole Diameter:Between 0.276 inches and 0.283 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Length:
 8.000 inches Body Width: Between 2.970 inches and 3.030 inches Unthreaded Mounting Hole Diameter: Between 0.276 inches and 0.283 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Body Width: Between 2.970 inches and 3.030 inches Unthreaded Mounting Hole Diameter: Between 0.276 inches and 0.283 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 2.970 inches and 3.030 inches Unthreaded Mounting Hole Diameter: Between 0.276 inches and 0.283 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Unthreaded Mounting Hole Diameter: Between 0.276 inches and 0.283 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 0.276 inches and 0.283 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
9.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.000 inches
Operating Tempurature Range:
-55.0/+78.0 degrees celsius
Source Impedance Rating Per Function:
50.0 ohms 4th radio interference
Load Impedance Per Function:
50.0 ohms 5th radio interference
Power Line Frequency Rating Per Function In Hertz:
60.0 3rd radio interference
Operating Current Rating Per Function In Amps:
14.0 5th radio interference
Maximum Voltage Drop Per Function:
500.0 millivolts dc 5th radio interference
Maximum Tempurature Rise:
40.0 degrees celsius
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 unthreaded hole
Functional Terminal Type And Quantity:
5 threaded stud output 2nd function
Operating Voltage Rating And Type Per Function:
115.0 volts ac 3rd radio interference 3rd function
Body Material:
Metal
Maximum Dielectric Withstanding Dc Voltage:
600.0 volts at sea level
Style Designator:
Rectangular terminal/terminals on opposite surfaces

Radio Frequency Interference Filter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0