

View Online at https://aerobasegroup.com/nsn/5915-01-025-0866

Overall Height:3.301 inchesBody Length:1.500 inchesBody Width:1.500 inchesBody Height:2.200 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Length:0.875 inchesVibration Resistance Range In Hertz:+10.0/+500.0Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:0.875 inchesVibration Resistance Range In Hertz:+10.0/+500.0Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:0.875 inchesOperating Tempurature Range:-55.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms 2nd radio interferenceLoad Impedance Per Function:50.0 ohms 2nd radio interferencePower Line Frequency Rating Per Function In Hertz:60.0 2nd radio interference
Body Length:1.500 inchesBody Width:1.500 inchesBody Width:1.500 inchesBody Height:2.200 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Length:0.875 inchesVibration Resistance Range In Hertz:+10.0/+500.0Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:0.875 inchesOperating Tempurature Range:-55.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms 2nd radio interferenceLoad Impedance Per Function:50.0 ohms 2nd radio interferencePower Line Frequency Rating Per Function In Hertz:60.0 2nd radio interference
 1.500 inches Body Width: 1.500 inches Body Height: 2.200 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.875 inches Vibration Resistance Range In Hertz: +10.0/+500.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
Body Width: 1.500 inches Body Height: 2.200 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.875 inches Vibration Resistance Range In Hertz: +10.0/+500.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
1.500 inches Body Height: 2.200 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.875 inches Vibration Resistance Range In Hertz: +10.0/+500.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Fower Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
Body Height: 2.200 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.875 inches Vibration Resistance Range In Hertz: +10.0/+500.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
2.200 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.875 inches Vibration Resistance Range In Hertz: +10.0/+500.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.875 inches Vibration Resistance Range In Hertz: +10.0/+500.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
0.875 inches Vibration Resistance Range In Hertz: +10.0/+500.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
 Vibration Resistance Range In Hertz: +10.0/+500.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
+10.0/+500.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
0.875 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
-55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference
60.0 2nd radio interference
Operating Current Rating Per Function In Amps:
0.25 1st radio interference
Maximum Voltage Drop Per Function:
250.0 millivolts ac 2nd radio interference
Input Terminal Manufacturer Code:
96906
Input Terminal Identification:
Ms3443h10-6p
Maximum Tempurature Rise:
25.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded hole
Functional Terminal Type And Quantity:
2 turret output 2nd function
Operating Voltage Rating And Type Per Function:



Thread Size:

0.112 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Unpackaged Unit Weight:

12.000 ounces

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0