## NSN 5915-01-028-0233

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-028-0233

Overall Height:
2.250 inches
Body Length:
1.688 inches
Body Width:
1.188 inches
Body Height:
1.625 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Operating Tempurature Range:
+0.0/+85.0 degrees celsius
Reference Frequency Per Function:
250.0 hertz blank
Input Impedance Per Function W/load:
10.0 kilohms blank
Output Impedance Per Function W/source Across Input:
10.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
3.0 blank
Functional Terminal Type And Quantity:
1 turret output 2nd function
Maximum Dielectric Withstanding Ac Rms Voltage:
500.0 volts at sea level
Specified Frequencies Of Discrimination Per Function:
100.00 hertz blank and 400.00 hertz blank and 600.00 hertz blank and 800.00 hertz blank
Thread Size:
0.138 inches
Body Material:
Metal
Frequency Band Width Per Function:
100.00 hertz blank and 400.00 hertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 6.0 blank and 35.0 blank and 40.0 blank

## NSN 5915-01-028-0233

Low Pass Filter - Page 2 of 2



Style	Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0