NSN 5915-01-028-5858

Band Pass Filter - Page 1 of 2

Style Designator:

Rectangular terminal/terminals on one surface



View Online at https://aerobasegroup.com/nsn/5915-01-028-5858

| Oursell Heights |
|---|
| Overall Height: 1.355 inches |
| |
| Body Length: |
| 1.000 inches |
| Body Width: |
| 0.875 inches |
| Body Height: |
| 0.960 inches |
| Vibration Resistance Range In Hertz: |
| +10.0/+55.0 |
| Operating Tempurature Range: |
| +0.0/+65.0 degrees celsius |
| Average Life Rating In Hours: |
| 20000.0 |
| Reference Frequency Per Function: |
| 5.432 megahertz blank |
| Source Impedance Rating Per Function: |
| 1.0 kilohms blank |
| Load Impedance Per Function: |
| 3.01 kilohms blank |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 1 threaded hole |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 1.0 blank |
| Functional Terminal Type And Quantity: |
| 1 pin output 2nd function |
| Specified Frequencies Of Discrimination Per Function: |
| 5.425 megahertz blank and 5.429 megahertz blank and 5.435 megahertz blank and 5.439 megahertz blank |
| Thread Size: |
| 0.112 inches |
| Body Material: |
| Metal |
| Frequency Band Width Per Function: |
| 5.429 megahertz blank and 5.435 megahertz blank |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |
| 20.0 blank and 3.0 blank and 20.0 blank |

NSN 5915-01-028-5858

Band Pass Filter - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0