Band Suppression Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-028-5870

Overall Height:
1.310 inches
Body Length:
3.500 inches
Body Width:
1.500 inches
Body Height:
1.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
3.125 inches
Vibration Resistance Range In Hertz:
+10.0/+55.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.125 inches
Operating Tempurature Range:
+0.0/+85.0 degrees celsius
Average Life Rating In Hours:
40000.0
Reference Frequency Per Function:
10.4 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
4.0 blank
Functional Terminal Type And Quantity:
2 pin ground 3rd function
Specified Frequencies Of Discrimination Per Function:
10.397 megahertz blank and 10.3995 megahertz blank and 10.4005 megahertz blank and 10.403 megahertz blank
Thread Size:
0.112 inches
Body Material:
Metal
Frequency Band Width Per Function:
10.3995 megahertz blank and 10.4005 megahertz blank

# NSN 5915-01-028-5870

Band Suppression Filter - Page 2 of 2



### Discrimination At Specificationified Frequencies Per Function In Decibels:

1.5 blank and 50.0 blank and 50.0 blank and 1.5 blank

#### Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A047b0