## NSN 5915-01-030-7006

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-030-7006

Overall Height:
1.005 inches
Body Length:
2.000 inches
Body Width:
2.000 inches
Body Height:
0.600 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.600 inches
Vibration Resistance Range In Hertz:
+10.0/+55.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.600 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Average Life Rating In Hours:
20000.0
Reference Frequency Per Function:
267.1 kilohertz blank
Source Impedance Rating Per Function:
2.2 kilohms blank
Load Impedance Per Function:
2.2 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
6.0 blank
Functional Terminal Type And Quantity:
1 pin output 2nd function
Specified Frequencies Of Discrimination Per Function:
94.00 kilohertz blank and 224.10 kilohertz blank and 310.10 kilohertz blank and 505.00 kilohertz blank
Thread Size:
0.112 inches
Frequency Band Width Per Function:
224.10 kilohertz blank and 310.10 kilohertz blank

50.0 blank and 1.0 blank and 1.0 blank and 50.0 blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

## NSN 5915-01-030-7006

Band Pass Filter - Page 2 of 2



Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0