## NSN 5915-01-032-4475

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-032-4475 **Overall Height:** 0.812 inches **Body Length:** 2.000 inches **Body Width:** 2.000 inches **Body Height:** 0.500 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.500 inches **Vibration Resistance Range In Hertz:** +5.0/+55.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Reference Frequency Per Function:** 5.0 kilohertz blank **Source Impedance Rating Per Function:** 50.0 ohms blank **Load Impedance Per Function:** 50.0 ohms blank **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type:** Encased **Mounting Facility Type And Quantity:** 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank **Functional Terminal Type And Quantity:** 2 pin output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 100.0 volts at altitude **Specified Frequencies Of Discrimination Per Function:** 1.00 hertz blank and 10.00 kilohertz blank and 20.00 kilohertz blank and 40.00 kilohertz blank **Thread Size:** 0.112 inches

**Body Material:** 

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 10.00 kilohertz blank

## NSN 5915-01-032-4475

Low Pass Filter - Page 2 of 2



Discrimination	At Specificationified I	Fraguancias Par	Function In	Decibals:
Discrimination	At Specificationified i	rieduelicies rei	runction in	Decibeis.

1.0 blank and 1.0 blank and 60.0 blank and 60.0 blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0