

View Online at https://aerobasegroup.com/nsn/5915-01-034-6470

0.962 inches Body Length: 0.612 inches Operating Current Rating Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 40.0 millivolts dc blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Width Across Flats: Between 0.190 inches and 0.210 inches Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Body Length: 0.612 inches Operating Current Rating Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 40.0 millivolts dc blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Width Across Flats: Between 0.190 inches and 0.210 inches Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Overall Length:
0.612 inches Operating Current Rating Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 40.0 millivolts dc blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Width Across Flats: Between 0.190 inches and 0.210 inches Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	0.962 inches
Operating Current Rating Per Function In Amps: 10.0 blank Maximum Voltage Drop Per Function: 40.0 millivolts dc blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Width Across Flats: Between 0.190 inches and 0.210 inches Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Body Length:
10.0 blank Maximum Voltage Drop Per Function: 40.0 millivolts dc blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Width Across Flats: Between 0.190 inches and 0.210 inches Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	0.612 inches
Maximum Voltage Drop Per Function: 40.0 millivolts dc blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Width Across Flats: Between 0.190 inches and 0.210 inches Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Operating Current Rating Per Function In Amps:
40.0 millivolts dc blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Width Across Flats: Between 0.190 inches and 0.210 inches Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	10.0 blank
Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Width Across Flats: Between 0.190 inches and 0.210 inches Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Maximum Voltage Drop Per Function:
Unf Inclosure Type: Hermetically sealed Width Across Flats: Between 0.190 inches and 0.210 inches Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	40.0 millivolts dc blank
Inclosure Type: Hermetically sealed Width Across Flats: Between 0.190 inches and 0.210 inches Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Mounting Facility Screw Thread Series Designator:
Hermetically sealed Width Across Flats: Between 0.190 inches and 0.210 inches Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Unf
Width Across Flats: Between 0.190 inches and 0.210 inches Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Inclosure Type:
Between 0.190 inches and 0.210 inches Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Hermetically sealed
Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Width Across Flats:
1 threaded bushing Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Between 0.190 inches and 0.210 inches
Functional Terminal Type And Quantity: 2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Mounting Facility Type And Quantity:
2 tab, solder lug ground Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	1 threaded bushing
Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Functional Terminal Type And Quantity:
50.0 volts dc blank Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	2 tab, solder lug ground
Thread Size: 0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Operating Voltage Rating And Type Per Function:
0.250 inches Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	50.0 volts dc blank
Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Thread Size:
Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	0.250 inches
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Round terminal/terminals on opposite surfaces
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
 Demilitarization: Yes - demil/mli Fiig:	N/a
Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	
Fiig:	Demilitarization:
0	Yes - demil/mli
A047b0	Fiig:
	A047b0