NSN 5915-01-036-5580

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-036-5580

Oursell Heights
Overall Height:
2.000 inches
Body Length:
2.250 inches
Body Width:
0.860 inches
Body Height:
1.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.500 inches
Source Impedance Rating Per Function:
50.0 ohms 2nd radio interference
Load Impedance Per Function:
50.0 ohms 2nd radio interference
Power Line Frequency Rating Per Function In Hertz:
400.0 2nd radio interference
Operating Current Rating Per Function In Amps:
5.0 2nd radio interference
Principal Circuitry Type Per Function:
Inductance-capacitance 2nd radio interference
Input Terminal Manufacturer Code:
70903
Input Terminal Identification:
17258-s
Full Load Insertion Loss Frequencies In Megahertz:
0.15 and 0.3 and 0.5 and 1.0 and 10.0 and 1000.0
Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:
52.0 and 70.0 and 90.0 and 90.0 and 80.0
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
2 threaded hole
Functional Terminal Type And Quantity:
2 tab, solder lug output 2nd function
Operating Voltage Rating And Type Per Function:
130.0 volts ac 1st radio interference 1st function and 400.0 volts dc 1st radio interference 1st function
Thread Size:
0.138 inches

Rectangular terminal/terminals on opposite surfaces

NSN 5915-01-036-5580

Radio Frequency Interference Filter - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0