Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-037-7814

Overall Length:	
3.294 inches	
Body Length:	
2.062 inches	
Body Outside Diameter:	
0.750 inches	
Operating Tempurature Range:	
-35.0/+95.0 degrees celsius	
Average Life Rating In Hours:	
10000.0	
Reference Frequency Per Function:	
4.3 lead styphnate bead two phase to two phase	
Input Impedance Per Function W/load:	
91.0 ohms 1st low pass	
Output Impedance Per Function W/source Across Input:	
91.0 ohms 2nd low pass	
Principal Circuitry Type Per Function:	
Inductance-capacitance 2nd low pass	
Mounting Facility Screw Thread Series Designator:	
Unf	
Inclosure Type:	
Encased	
Mounting Facility Type And Quantity:	
1 threaded bushing	
Insertion Loss At Reference Frequency Per Function In Decibels:	
3.0 1st low pass	
Functional Terminal Type And Quantity:	
1 threaded stud output 2nd function	
Specified Frequencies Of Discrimination Per Function:	
3.46 megahertz 2nd low pass and 5.18 megahertz 2nd low pass and 5.50 megahertz 2nd low pass and 6.90 megahertz 2nd low p	ass
Thread Size:	
0.190 inches	
Body Material:	
Metal	
Frequency Band Width Per Function:	
3.46 megahertz 2nd low pass	
Discrimination At Specificationified Frequencies Per Function In Decibels:	
3.0 2nd low pass and 3.0 2nd low pass and 70.0 2nd low pass and 70.0 2nd low pass	
Style Designator:	
Round terminal/terminals on opposite surfaces	
Shelf Life:	
N/a	

NSN 5915-01-037-7814

Low Pass Filter - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A047b0

