## NSN 5915-01-038-6192

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-038-6192 **Body Length:** 1.688 inches **Body Width:** 1.188 inches **Body Height:** 3.125 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches **Reference Frequency Per Function:** 28.0 7th high pass two phase to two phase **Source Impedance Rating Per Function:** 10.0 kilohms 1st low pass **Load Impedance Per Function:** 10.0 kilohms 3rd low pass **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type: Encased Mounting Facility Type And Quantity:** 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 2.0 3rd low pass **Functional Terminal Type And Quantity:** 1 standard tube base input-output/ground **Specified Frequencies Of Discrimination Per Function:** 1.00 hertz 3rd low pass and 110.00 hertz 3rd low pass and 187.00 hertz 3rd low pass and 374.00 hertz 3rd low pass **Thread Size:** 0.138 inches **Frequency Band Width Per Function:** 1.00 hertz 3rd low pass and 110.00 hertz 3rd low pass Discrimination At Specificationified Frequencies Per Function In Decibels: 6.0 1st low pass and 6.0 1st low pass and 50.0 1st low pass and 60.0 1st low pass Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a

**Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 5915-01-038-6192

Low Pass Filter - Page 2 of 2



Fiig:

A047b0