

View Online at <https://aerobasegroup.com/nsn/5915-01-038-7943>

Overall Height:

0.940 inches

Body Length:

2.000 inches

Body Width:

0.780 inches

Body Height:

0.765 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.600 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.450 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

505.0 hertz blank

Source Impedance Rating Per Function:

3.9 kilohms blank

Load Impedance Per Function:

47.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

1.5 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

10.00 hertz blank and 1.00 kilohertz blank and 12.50 kilohertz blank and 5.00 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

10.00 hertz blank and 1.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 70.0 blank and 90.0 blank

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Unpackaged Unit Weight:

60.000 grams

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0