

View Online at <https://aerobasegroup.com/nsn/5915-01-039-7121>

Overall Length:

3.900 inches

Body Outside Diameter:

0.500 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Reference Frequency Per Function:

375.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Input Terminal Manufacturer Code:

94990

Input Terminal Identification:

Sma

Output Terminal Manufacturer Code:

94990

Output Terminal Identification:

Sma

Voltage Standing Wave Ratio Per Function:

2.0 blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 connector

Insertion Loss At Reference Frequency Per Function In Decibels:

1.5 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

304.75 megahertz blank and 363.75 megahertz blank and 386.25 megahertz blank and 435.00 megahertz blank

Frequency Band Width Per Function:

363.75 megahertz blank and 386.25 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

55.0 blank and 1.0 blank and 1.0 blank and 55.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

363.75 megahertz blank and 386.25 megahertz blank

Special Features:

4 poles

Unpackaged Unit Weight:

80.000 grams

Style Designator:

Round terminal/terminals on opposite surfaces

Test Data Document:

94990-25-+04275f drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0