

View Online at <https://aerobasegroup.com/nsn/5915-01-039-7121>

**Overall Length:**

3.900 inches

**Body Outside Diameter:**

0.500 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-54.0/+85.0 degrees celsius

**Reference Frequency Per Function:**

375.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Input Terminal Manufacturer Code:**

94990

**Input Terminal Identification:**

Sma

**Output Terminal Manufacturer Code:**

94990

**Output Terminal Identification:**

Sma

**Voltage Standing Wave Ratio Per Function:**

2.0 blank

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 connector

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.5 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

304.75 megahertz blank and 363.75 megahertz blank and 386.25 megahertz blank and 435.00 megahertz blank

**Frequency Band Width Per Function:**

363.75 megahertz blank and 386.25 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

55.0 blank and 1.0 blank and 1.0 blank and 55.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

363.75 megahertz blank and 386.25 megahertz blank

**Special Features:**

4 poles

**Unpackaged Unit Weight:**

80.000 grams

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Test Data Document:**

94990-25-+04275f drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0