

View Online at <https://aerobasegroup.com/nsn/5915-01-041-3680>

Overall Length:

3.812 inches

Mounting Slot Width:

0.250 inches

Body Length:

3.687 inches

Body Width:

2.312 inches

Body Height:

1.625 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Average Life Rating In Hours:

5000.0

Reference Frequency Per Function:

20.006 kilohertz blank

Source Impedance Rating Per Function:

35.0 ohms blank

Load Impedance Per Function:

35.0 ohms blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance-resistance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

2.5 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

19.320 kilohertz blank and 19.773 kilohertz blank and 20.239 kilohertz blank and 20.690 kilohertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

19.773 kilohertz blank and 20.239 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

80.0 blank and 3.0 blank and 3.0 blank and 80.0 blank

Special Features:

Terminated by a parallel combination of a 200 k ohm p or m 10 pct resistor and a 100 pf capacitor, 1.500 in. Distance between mtg holes parallel to body w

Precious Material And Location:

Terminals electro plated gold

Precious Material:

Gold

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0