

View Online at <https://aerobasegroup.com/nsn/5915-01-043-4387>

Overall Height:

1.108 inches

Body Length:

2.000 inches

Body Width:

1.000 inches

Body Height:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.000 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+91.0 degrees celsius

Average Life Rating In Hours:

1000.0

Reference Frequency Per Function:

18.0 megahertz blank

Source Impedance Rating Per Function:

5.0 kilohms blank

Load Impedance Per Function:

2.5 kilohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

17.9835 megahertz blank and 17.991 megahertz blank and 18.009 megahertz blank and 18.0165 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

17.991 megahertz blank and 18.009 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

Special Features:

Terminals 1 and 3 ground; common to case

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Test Data Document:

13499-293-1234 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0