

View Online at https://aerobasegroup.com/nsn/5915-01-043-4388

| Overall Length: |
|--|
| 1.700 inches |
| Body Length: |
| 0.952 inches |
| Body Outside Diameter: |
| 0.687 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Source Impedance Rating Per Function: |
| 50.0 ohms blank |
| Load Impedance Per Function: |
| 50.0 ohms blank |
| Power Line Frequency Rating Per Function In Hertz: |
| 60.0 blank |
| Operating Current Rating Per Function In Amps: |
| 1.0 blank |
| Maximum Voltage Drop Per Function: |
| 0.4 volts dc blank |
| Principal Circuitry Type Per Function: |
| Capacitance-inductance blank |
| Mounting Facility Screw Thread Series Designator: |
| Unf |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 1 threaded bushing |
| Functional Terminal Type And Quantity: |
| 1 tab, solder lug output 2nd function |
| Maximum Dielectric Withstanding Ac Rms Voltage: |
| 480.0 volts at sea level |
| Operating Voltage Rating And Type Per Function: |
| 240.0 volts ac blank |
| Thread Size: |
| 0.312 inches |
| Body Material: |
| Metal |
| Style Designator: |
| Round terminal/terminals on opposite surfaces |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

Radio Frequency Interference Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0