

View Online at https://aerobasegroup.com/nsn/5915-01-046-9285

Overall Length:
5.858 inches
Body Length:
4.562 inches
Body Outside Diameter:
1.395 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Average Life Rating In Hours:
250.0
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
400.0 blank
Operating Current Rating Per Function In Amps:
20.0 blank
Maximum Voltage Drop Per Function:
160.0 millivolts ac blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Maximum Tempurature Rise:
25.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded bushing
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Operating Voltage Rating And Type Per Function:
125.0 volts ac blank and 400.0 volts dc blank
Thread Size:
0.750 inches
Body Material:
Metal
Body Surface Treatment:
Tin



## Style Designator:

Round terminal/terminals on opposite surfaces

## Test Data Document:

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-f-15733/41 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A047b0