NSN 5915-01-046-9296

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-046-9296

Overall Length:

Between 5.105 inches and 5.644 inches

Body Length:

Between 4.980 inches and 5.020 inches

Body Width:

Between 2.980 inches and 3.020 inches

Body Height:

Between 0.720 inches and 0.850 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 4.490 inches and 4.510 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.490 inches and 2.510 inches

Operating Tempurature Range:

+0.0/+150.0 degrees fahrenheit

Reference Frequency Per Function:

14.0 kilohertz blank

Input Impedance Per Function W/load:

75.0 ohms blank

Output Impedance Per Function W/source Across Input:

75.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

4.00 kilohertz blank and 24.00 kilohertz blank and 28.40 kilohertz blank and 1.00 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

4.00 kilohertz blank and 24.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 20.0 blank and 20.0 blank

Unpackaged Unit Weight:

1.000 pounds

NSN 5915-01-046-9296

Low Pass Filter - Page 2 of 2



Fiig:

No

A047b0