# NSN 5915-01-046-9296

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-046-9296

# **Overall Length:**

Between 5.105 inches and 5.644 inches

# Body Length:

Between 4.980 inches and 5.020 inches

# Body Width:

Between 2.980 inches and 3.020 inches

#### **Body Height:**

Between 0.720 inches and 0.850 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 4.490 inches and 4.510 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.490 inches and 2.510 inches

#### **Operating Tempurature Range:**

+0.0/+150.0 degrees fahrenheit

#### **Reference Frequency Per Function:**

14.0 kilohertz blank

### Input Impedance Per Function W/load:

75.0 ohms blank

### **Output Impedance Per Function W/source Across Input:**

75.0 ohms blank

### Mounting Facility Screw Thread Series Designator:

Unc

### Inclosure Type:

Encased

### Mounting Facility Type And Quantity:

4 threaded hole

### Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

### Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

### Specified Frequencies Of Discrimination Per Function:

4.00 kilohertz blank and 24.00 kilohertz blank and 28.40 kilohertz blank and 1.00 megahertz blank

#### Thread Size:

0.112 inches

### **Body Material:**

Metal

### Frequency Band Width Per Function:

4.00 kilohertz blank and 24.00 kilohertz blank

## Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 20.0 blank and 20.0 blank

## Unpackaged Unit Weight:

1.000 pounds

# NSN 5915-01-046-9296

Low Pass Filter - Page 2 of 2



Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A047b0