NSN 5915-01-051-2511

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-051-2511 **Overall Length:** 4.750 inches **Body Outside Diameter:** 0.750 inches **Vibration Resistance Range In Hertz:** +5.0/+55.0 **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Reference Frequency Per Function:** 1.1 gigahertz blank **Source Impedance Rating Per Function:** 50.0 ohms blank **Load Impedance Per Function:** 50.0 ohms blank **Voltage Standing Wave Ratio Per Function:** 1.2 blank **Inclosure Type:** Encased **Mounting Facility Type And Quantity:** 2 connector Insertion Loss At Reference Frequency Per Function In Decibels: 0.5 blank **Functional Terminal Type And Quantity:** 1 connector, receptacle output 2nd function **Specified Frequencies Of Discrimination Per Function:** 950.00 megahertz blank and 1.25 gigahertz blank and 1.922 gigahertz blank and 3.844 gigahertz blank **Body Material:** Metal **Frequency Band Width Per Function:** 950.00 megahertz blank and 1.25 gigahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 1.0 blank and 1.0 blank and 40.0 blank and 40.0 blank **Voltage Standing Wave Ratio Frequency Limits Per Function:** 950.0 megahertz blank and 1.25 gigahertz blank **Style Designator:** Round terminal/terminals on opposite surfaces Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5915-01-051-2511

Low Pass Filter - Page 2 of 2



Fiig:

A047b0