NSN 5915-01-052-5167

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-052-5167

| Overall Length: |
|---|
| 2.625 inches |
| Overall Height: |
| 1.625 inches |
| Overall Width: |
| 1.625 inches |
| Inside Width: |
| 1.280 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.169 inches |
| Vibration Resistance Range In Hertz: |
| +5.0/+25.0 |
| Inside Height: |
| 1.220 inches |
| Reference Frequency Per Function: |
| 10.37 gigahertz blank |
| Input Impedance Per Function W/load: |
| 50.0 ohms blank |
| Output Impedance Per Function W/source Across Input: |
| 50.0 ohms blank |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 0.4 blank |
| Functional Terminal Type And Quantity: |
| 1 rectangular flange input-output |
| Specified Frequencies Of Discrimination Per Function: |
| 9.84 gigahertz blank and 10.24 gigahertz blank and 10.50 gigahertz blank and 10.915 gigahertz blank |
| Frequency Band Width Per Function: |
| 10.24 gigahertz blank and 10.50 gigahertz blank |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |
| 20.0 blank and 1.0 blank and 20.0 blank |
| Body Surface Treatment: |
| Cadmium |
| Precious Material And Location: |
| Interior surfaces gold and interior surfaces silver |
| Precious Material: |
| Gold and silver |
| Style Designator: |
| Rectangular terminal/terminals on opposite surfaces |

NSN 5915-01-052-5167

Band Pass Filter - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0