

View Online at <https://aerobasegroup.com/nsn/5915-01-053-6529>

**Overall Length:**

3.406 inches

**Body Length:**

2.359 inches

**Body Outside Diameter:**

1.250 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Power Line Frequency Rating Per Function In Hertz:**

400.0 blank

**Operating Current Rating Per Function In Amps:**

10.0 blank

**Maximum Voltage Drop Per Function:**

0.3 volts dc blank

**Principal Circuitry Type Per Function:**

Capacitance-inductance blank

**Maximum Temperature Rise:**

25.0 degrees celsius

**Full Load Insertion Loss Frequencies In Megahertz:**

0.15 and 0.5 and 1.0 and 10.0 and 100.0 and 400.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

60.0 and 88.0 and 100.0 and 85.0 and 85.0 and 85.0

**Mounting Facility Screw Thread Series Designator:**

Unef

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

1 threaded stud

**Features Provided:**

Nut and washer

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:**

125.0 volts ac blank and 400.0 volts dc blank

**Thread Size:**

0.625 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

250.0 volts at sea level

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0