NSN 5915-01-058-1323

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-058-1323

Overall Length:
1.420 inches
Overall Height:
0.520 inches
Body Length:
1.020 inches
Body Width:
0.770 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.730 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.480 inches
Operating Tempurature Range:
-25.0/+50.0 degrees celsius
Reference Frequency Per Function:
30.0 megahertz blank
Input Impedance Per Function W/load:
50.0 ohms blank
Output Impedance Per Function W/source Across Input:
50.0 ohms blank
Voltage Standing Wave Ratio Per Function:
1.5 blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
2 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
2.0 blank
Functional Terminal Type And Quantity:
2 solder stud ground 3rd function
Specified Frequencies Of Discrimination Per Function:
25.00 megahertz blank and 35.00 megahertz blank and 50.00 megahertz blank and 100.00 megahertz blank
Thread Size:
0.112 inches
Frequency Band Width Per Function:
25.00 megahertz blank and 35.00 megahertz blank

1.0 blank and 1.0 blank and 40.0 blank and 40.0 blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

NSN 5915-01-058-1323

Low Pass Filter - Page 2 of 2



Sty	le	Desi	ign	ato	r:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0