

View Online at <https://aerobasegroup.com/nsn/5915-01-059-6753>

Overall Length:

Between 0.967 inches and 1.008 inches

Body Length:

Between 0.509 inches and 0.571 inches

Body Outside Diameter:

Between 0.365 inches and 0.385 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Operating Current Rating Per Function In Amps:

1.0 blank

Maximum Voltage Drop Per Function:

0.25 volts dc blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded bushing

Functional Terminal Type And Quantity:

1 tab, solder lug input and 1 tab, solder lug output

Operating Voltage Rating And Type Per Function:

50.0 volts dc blank

Thread Size:

0.250 inches

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Body Surface Treatment:

Tin

Special Features:

W/int tooth lockwasher 0.025 in. Thk x 0.405 in. Dia

Style Designator:

Round terminal/terminals on opposite surfaces

Test Data Document:

98230-0n241893-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0