

View Online at <https://aerobasegroup.com/nsn/5915-01-059-6754>

**Overall Length:**

Between 1.443 inches and 1.503 inches

**Body Length:**

Between 0.732 inches and 0.794 inches

**Body Outside Diameter:**

0.385 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Operating Current Rating Per Function In Amps:**

0.25 blank

**Maximum Voltage Drop Per Function:**

1.0 volts dc blank

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Functional Terminal Type And Quantity:**

1 tab, solder lug input and 1 tab, solder lug output

**Operating Voltage Rating And Type Per Function:**

250.0 volts dc blank

**Thread Size:**

0.250 inches

**Maximum Dielectric Withstanding Dc Voltage:**

100.0 volts at sea level

**Body Surface Treatment:**

Tin

**Special Features:**

W/intl tooth lockwasher 0.025 in.Thk x 0.405 in. Dia

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Test Data Document:**

98230-0n241893-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0