

View Online at <https://aerobasegroup.com/nsn/5915-01-061-1509>

Overall Length:

0.831 inches

Body Length:

0.491 inches

Body Outside Diameter:

0.415 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Average Life Rating In Hours:

250.0

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Operating Current Rating Per Function In Amps:

15.0 blank

Maximum Voltage Drop Per Function:

120.0 millivolts dc blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

7.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded bushing

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

50.0 volts dc blank

Thread Size:

0.250 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Unpackaged Unit Weight:

5.000 grams

Style Designator:

Round terminal/terminals on opposite surfaces

Test Data Document:

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-15733/38 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0