## NSN 5915-01-062-0591

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-062-0591

Overall Height:
1.036 inches
Body Length:
3.500 inches
Body Width:
0.880 inches
Body Height:
0.630 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
3.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.500 inches
Operating Tempurature Range:
+25.0/+45.0 degrees celsius
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
362.5 kilohertz blank
Source Impedance Rating Per Function:
100.0 ohms blank
Load Impedance Per Function:
100.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
1.0 blank
Functional Terminal Type And Quantity:
2 pin ground 3rd function
Specified Frequencies Of Discrimination Per Function:
225.00 kilohertz blank and 500.00 kilohertz blank and 640.00 kilohertz blank and 1.25 megahertz blank
Thread Size:
0.138 inches
Body Material:
Metal
Frequency Band Width Per Function:
225.00 kilohertz blank and 500.00 kilohertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 18.6 blank and 30.0 blank and 60.0 blank

## NSN 5915-01-062-0591

Low Pass Filter - Page 2 of 2



Style	De	sia	nato	r:
	-	9.9	···	

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0