

View Online at <https://aerobasegroup.com/nsn/5915-01-064-1463>

**Overall Height:**

0.575 inches

**Body Length:**

2.750 inches

**Body Width:**

0.688 inches

**Body Height:**

0.375 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.562 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.500 inches

**Operating Temperature Range:**

-54.0/+85.0 degrees celsius

**Reference Frequency Per Function:**

160.0 megahertz blank

**Input Impedance Per Function W/load:**

50.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

50.0 ohms blank

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

9.0 blank

**Functional Terminal Type And Quantity:**

2 pin ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

130.00 megahertz blank and 157.50 megahertz blank and 162.50 megahertz blank and 190.00 megahertz blank

**Thread Size:**

0.086 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

157.50 megahertz blank and 162.50 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

70.0 blank and 3.0 blank and 3.0 blank and 70.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

157.5 megahertz blank and 162.5 megahertz blank

**Unpackaged Unit Weight:**

2.000 ounces

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A047b0