NSN 5915-01-064-1463



View Online at https://aerobasegroup.com/nsn/5915-01-064-1463

Band Pass Filter - Page 1 of 2 **Overall Height:** 0.575 inches **Body Length:** 2.750 inches **Body Width:** 0.688 inches **Body Height:** 0.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.500 inches **Operating Tempurature Range:** -54.0/+85.0 degrees celsius **Reference Frequency Per Function:** 160.0 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank **Output Impedance Per Function W/source Across Input:** 50.0 ohms blank **Voltage Standing Wave Ratio Per Function:** 1.5 blank Mounting Facility Screw Thread Series Designator: Unc **Inclosure Type:** Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 9.0 blank **Functional Terminal Type And Quantity:** 2 pin ground 3rd function **Specified Frequencies Of Discrimination Per Function:**

130.00 megahertz blank and 157.50 megahertz blank and 162.50 megahertz blank and 190.00 megahertz blank

Thread Size:

0.086 inches

Body Material:

Metal

Frequency Band Width Per Function:

157.50 megahertz blank and 162.50 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

70.0 blank and 3.0 blank and 3.0 blank and 70.0 blank

NSN 5915-01-064-1463

Band Pass Filter - Page 2 of 2



Voltage Standing Wave Ratio Frequency Limits Per Function:

157.5 megahertz blank and 162.5 megahertz blank

Unpackaged Unit Weight:

2.000 ounces

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0