

View Online at <https://aerobasegroup.com/nsn/5915-01-067-1276>

Overall Height:

0.930 inches

Body Length:

0.930 inches

Body Width:

0.505 inches

Body Height:

0.770 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.600 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.100 inches

Operating Temperature Range:

-46.0/+85.0 degrees celsius

End Application:

Uwasp class lhd; osprey class mhc; radio set (an/mrc-138); nimitz class cvn' whidbey class lsd; airborne mobile dir air spt ctl (21d), (02m jul 83) (an/uyq-3a); radio set (a1815) (an/grc-193); forrestal class cv; supply class aoe

Reference Frequency Per Function:

75.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

5.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

50.00 megahertz blank and 74.925 megahertz blank and 75.075 megahertz blank and 75.15 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

74.925 megahertz blank and 75.075 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

50.0 blank and 3.0 blank and 3.0 blank and 50.0 blank

Body Surface Treatment:

Tin

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0