

View Online at <https://aerobasegroup.com/nsn/5915-01-067-8364>

**Overall Height:**

1.030 inches

**Body Length:**

2.000 inches

**Body Width:**

1.600 inches

**Body Height:**

0.780 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.100 inches

**Operating Temperature Range:**

-46.0/+87.0 degrees celsius

**End Application:**

Whidbey island class lsd; nimitz class cvn; airborne mobile dir air spt ctl (21d), (02m jul 83) (an/uyq-3a); radio set (a185) (an/grc-193); wasp class lhd; radio set (an/mrc-138); forrestal class cv; supply class aoe; osprey class mhc

**Reference Frequency Per Function:**

3.0 kilohertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Inclosure Type:**

Encased

**Insertion Loss At Reference Frequency Per Function In Decibels:**

5.0 blank

**Functional Terminal Type And Quantity:**

2 pin ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

1.00 kilohertz blank and 2.00 kilohertz blank and 4.00 kilohertz blank and 6.00 kilohertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

2.00 kilohertz blank and 4.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 5.0 blank and 5.0 blank and 60.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

2.0 kilohertz blank and 4.0 kilohertz blank

**Body Surface Treatment:**

Tin

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0